



Homelift

MODEL 6000 - BELT



MODEL 6000 - ROPE



MODEL 7000 - HYDRAULIC





Machine Roomless



Gearless & Belt



250 - 450 kg



0,15 m/s



20 m



2:1 or 1:1



**Single or 180 or 90
Degree Double
Entrance**



**L Type Cabin Frame
Pit: 200 mm
Overhead: 2600 mm**



**Machinery Directive
2006/42/EC**



Machine Roomless



Gearless & Rope



250 - 450 kg



0,15 m/s



20 m



2:1 or 1:1



**Single or 180 or 90
Degree Double
Entrance**



**L Type Cabin Frame
Pit: 200 mm
Overhead: 2600 mm**



**Machinery Directive
2006/42/EC**



Hydraulic



250 - 450 kg



0,15 m/s



20 m



2:1 or 1:1



Single or 180 or 90 Degree Double Entrance



**L Type Cabin Frame
Pit: 200 mm
Overhead: 2600 mm**



**Machinery Directive
2006/42/EC**



TECHNICAL TABLE (AUTOMATIC DOOR)

Model 6000/7000 Homelift Automatic door

	250	300	375	450
Capacity [kg]	3	4	5	6
No of Persons	3	4	5	6
Roping	2:1			
Shaft Width [mm]	1300	1400	1500	1600
Shaft Depth [mm]	1600*	1750*	1750*	1750*
	1810**	1960**	1960**	1960**
Pit [mm]	200	200	200	200
Overhead [mm]	2600	2600	2600	2600
Car Width [mm]	800	900	1000	1100
Car Depth [mm]	1250	1400	1400	1400
Car Internal Height [mm]	2050	2050	2050	2050
Door Type	2PT automatic			
Door Width [mm]	700	800	800	800
Door Height [mm]	2000	2000	2000	2000
Cabin DBG [mm]	875	975	975	975
CWT DBG [mm]	550	650	650	650
Max. Travel [m]	20			
Max. No of Stops	7			
Max. Speed [m/s]	0,15			
Car Entrances	Single			
Car Frame Type	L type			
Directive	Machinery Directive 2006/42/EC			

* Single entrance

**180°degree double entrance



TECHNICAL TABLE (SEMI-AUTOMATIC DOOR)

Model 6000/7000 Homelift Semi-automatic door

	250	300	375	450
Capacity [kg]				
No of Persons	3	4	5	6
Roping	2:1			
Shaft Width [mm]	1300	1400	1500	1600
Shaft Depth [mm]	1425*	1575*	1575*	1575*
	1460**	1610**	1610**	1610**
Pit [mm]	200	200	200	200
Overhead [mm]	2500	2500	2500	2500
Car Width [mm]	800	900	1000	1100
Car Depth [mm]	1250	1400	1400	1400
Car Internal Height [mm]	2050	2050	2050	2050
Door Type	Semi-automatic			
Door Width [mm]	700	800	800	800
Door Height [mm]	2000	2000	2000	2000
Cabin DBG [mm]	875	975	975	975
CWT DBG [mm]	550	650	650	650
Max. Travel [m]	20			
Max. No of Stops	7			
Max. Speed [m/s]	0,15			
Car Entrances	Single			
Car Frame Type	L type			
Directive	Machinery Directive 2006/42/EC			

* Single entrance

**180°degree double entrance